

## CUPA 12





- CUPA 12 is a grey slate with a smooth matt surface. This slate is noted for its exceptional consistency of thickness and surface appearance. Qualities that have made it a popular choice for large commercial projects. Split to an average thickness of 4 and 6 mm.
- · La Campa Quarry. Folgoso del Caurel (Lugo), Spain. In operation since 1972.
- · 15,000 Tons/year.

## Formats & Sizes





**Formats** 

Rectangular, Square, Half Moon, Schuppen, Fischuppen. Sawed at 90°.

Sizes (cm)

Between 20x20 & 60x30, according to formats.

- UK: 30x20, 40x20, 40x25, 46x22, 50x25 & 60x30.
  Germany: 20x20 Half Moon, 25x25 & 30x30, 40x20, 40x25, 50x25, 60x30. Schuppen 24x19. Fischuppen 22x15 & 30x19.
- \* If you are interested in other formats please contact our Customer Service department.



## Technical **Specifications**

CUPA 12 slates are in compliance with the following specifications:

- European Specifications: EN 12326
- British Standard: BS 680: Part 2
  French Specifications: P32.301 & P32.302

WATER ABSORPTION	0.27%
CONTENTS OF CARBONATE NON CARBONATED	-
Mor Characteristic	54
CARBONATES CONTENT	0.60%
THICKNESS	5 mm & 6 mm

## Grading

All natural slate should be graded into at least 3 thicknesses prior to being placed on the roof. To minimize the effect of any variation in shade, slate should be drawn from at least 2 pallets at time.

As with any natural product, slate is subject to variance, and any slates that are identified at the time of grading as problematic should be cut and used at the eaves or ridge of the roof.

For further information on fixing natural slate please contact your supplier or visit www.cupanaturalslate.co.uk















