

Uniclass L5214







- CUPA 25 is a blue black slate with a smooth surface. Split to an average thickness of 4.2mm & 5mm.
- · Chano Castiello Quarry. Benuza (Leon), Spain. In operation since 1991.
- · 4,500 Tons/year.

## Formats & Sizes





**Formats** Rectangular & Rounded.

Sizes (cm) Between 22x16 & 50x25, according to formats.

- UK: 40x25 & 50x25.France: 22x16, 25x18, 27x18, 30x20 & 32x22.Spain: 27x18, 30x20, 32x22 &35x25 Scallop.
- \* If you are interested in other formats please contact our Customer Service department,



## **Technical Specifications**

CUPA 25 slates are in compliance with the following specifications:

- European Specifications: EN 12326
- British Standard: BS 680: Part 2
  French Specifications: P32.301 & P32.302

WATER ABSORPTION	0.24%
CONTENTS OF CARBONATE NON CARBONATED	0.49%
Mor Characteristic	74
CARBONATES CONTENT	0.80%
THICKNESS	4.2 & 5mm

## Grading

All natural slate should be graded into at least 3 thicknesses prior to being placed on the roof. To minimize the effect of any variation in shade, slate should be drawn from at least 2 pallets at time.

As with any natural product, slate is subject to variance, and any slates that are identified at the time of grading as problematic should be cut and used at the eaves or ridge of the roof.

For further information on fixing natural slate please contact your supplier or visit www.cupanaturalslate.co.uk

















